

ONESOURCE INDIRECT TAX DETERMINATION

INSTALLATION GUIDE

ORACLE DATABASE AND JBOSS

5.13.X.X

Document Version 5

COPYRIGHT NOTICE

© 2023 Thomson Reuters. All rights reserved. Republication or redistribution of Thomson Reuters content, including by framing or similar means, is prohibited without the prior written consent of Thomson Reuters. Thomson Reuters and the Kinesis logo are trademarks of Thomson Reuters and its affiliated companies. [More information can be found here](#).

In compliance with the license agreements for the Open Source Libraries leveraged by Thomson Reuters, our customers can obtain copies of these libraries by contacting Customer Support at <https://tax.thomsonreuters.com/en/support>.

DOCUMENT HISTORY

VERSION NUMBER	VERSION DATE	SUMMARY
1	February 2021	Created first version of this guide for ONESOURCE Indirect Tax Determination 5.13.x.x.
2	January 26, 2022	Updated the supported Java versions to include version 1.11.
3	April 6, 2022	Time Eviction Cache support.
4	September 9, 2022	Updates to Clustering and Time Eviction Caching process.
5	November 29, 2023	For creating data sources, replaced the instructions for searching for the <i>jboss-oracle-xa-ds_example.txt</i> file in the Knowledgebase with instructions for how to create the file.

TABLE OF CONTENTS

Introduction	1
Who Should Read This Guide?	1
Resources	1
Style Conventions	2
Prerequisites	5
Review System Requirements	5
Java	5
Gathering Administrative Information	5
Download the Software	6
Configuring Your Database	7
Database Initialization Parameters	7
Database Character Set	7
Oracle Tablespaces and Users	7
Preparing Oracle for XA Transactions	9
Configuring JBoss Enterprise Edition	11
Modifying the Start-Up Parameters	11
Unix Example	12
Microsoft Windows Example	13
Creating Data Sources	13
Controlling HTTP Parameters	17
JDBC Driver	18
Deploying the Application	18
Duplicate Users	19
Running the Implementer	21
Starting the Installation	21
Checking the Installation Results	21
Installing Tax Content	23
Importing Content into Determination	23
Creating and Configuring a Company	24

Testing Your Installation	25
Clustering	27
Prerequisites	27
Determination Parameters	28
Module File	29
Standalone File	30
Properties File	30
UDP Multicast with Default Settings	31
UDP Multicast with Non-Default IP and Port Number	32
TCP Transport with Static List of Nodes (TCPPING)	33
Cluster XML File	34
Cluster Test	35
Time Eviction Cache	37
Performing Additional Configurations	39

INTRODUCTION

The ONESOURCE Indirect Tax Determination software is a highly scalable and reliable taxing service for all business applications needing consolidated tax determination, calculation, and recording. A three-tier application built on industry standard Java technology and state-of-the-art design principles, the Determination software is designed to optimize performance, reliability, interoperability, manageability, and security.

This guide explains how to install Determination version 5.13.x.x.

WHO SHOULD READ THIS GUIDE?

The installation requires the coordination of people in various roles. If you are responsible for overseeing the installation, make this guide available to the following contributors:

- Database administrator
- Application server administrator
- IT administrator
- Tax professional

RESOURCES

Several resources help you become familiar with ONESOURCE Indirect Tax Determination and master its features. Help is installed with the application. All documents are posted in [Indirect Tax Help and Support](#). To locate documents specific to your application, enter the search term "Determination documentation."

DETERMINATION RESOURCES	
Resource	Description
Help	This Help system gives assistance within Determination. Use Help after Determination is installed and configured.
Installation Guide	This guide is intended for technical users and contains complete details about how to install and configure Determination.
Platform Support	This describes the combinations of operating systems, databases, and application servers on which Determination operates.

DETERMINATION RESOURCES

Resource	Description
Product Support Lifecycle	This lists the end-of-life dates for products in the ONESOURCE Indirect Tax Suite.
Upgrade Guide	This guide describes the procedures for upgrading an instance of Determination and refers to configuration information in the <i>Installation Guide</i> .
Customization Guide	This guide is intended for technical users. It describes types of customization and shows examples.
Data Dictionary	This resource is intended for technical users. It contains a list of all the fields in the Determination database.
Sizing Guide	This guide is intended for technical users. It contains an architectural overview and discusses components, database, and server sizing.

Still can't find what you're looking for? Try these additional resources:

ONESOURCE RESOURCES

Resource	Description
Indirect Tax Help and Support https://www.thomsonreuters.com/en-us/help/onesource-indirect-tax.html	Search for answers in the Knowledge Base, enter product support tickets, and track support ticket history for you and your organization.
Indirect Tax Customer Center https://customercenter.sabrix.com/	Download ONESOURCE Indirect Tax software.
Other ONESOURCE Indirect Tax Products and Services https://tax.thomsonreuters.com/en/corporation-solutions/indirect-tax	Browse descriptions of other ONESOURCE Indirect Tax products and services.
Documentation Feedback onesource.indirect.tax.fb@thomsonreuters.com	Send feedback about ONESOURCE Indirect Tax documentation.

STYLE CONVENTIONS

We use the following special formatting throughout this guide:

Bold text indicates most user interface elements, such as:

- Data you are expected to enter, such as in a text field
- Pages, buttons, tabs, and field names
- Dialog boxes, drop-down lists, selections within lists, and check box titles
- Windows
- Menu items

Italic text indicates the following:

- File and folder names
- Java classes, PL/SQL objects and executable files
- Document titles

CAPITAL text indicates keyboard commands, such as ENTER, or database components.

`Courier` text indicates command-line input/output.

<brackets> indicate user entry. For example, <host> indicates you should replace the text and angle brackets with your server name.

Book titles are shown in italics and sections within a book are in quotation marks, such as "Starting the Installation" in the *ONESOURCE Indirect Tax Determination Installation Guide*.



This pencil symbol indicates suggestions or additional information.



This warning symbol indicates important text that you should review before proceeding.

↵ This carriage return symbol indicates that a single line of code is divided into multiple lines so you can read it. If you copy and paste code with these symbols, be sure to keep the code before and after the carriage return on the same line.

```
1  /* Code snippets have numbered lines with a gray background. */  
2  /* Be cautious if you copy lines from the code snippets-the l  
   ine numbers are included! */
```

PREREQUISITES

Complete the following tasks before you attempt to install and configure ONESOURCE Indirect Tax Determination:

[Review System Requirements \(page 5\)](#)

[Java \(page 5\)](#)

[Gathering Administrative Information \(page 5\)](#)

[Download the Software \(page 6\)](#)

REVIEW SYSTEM REQUIREMENTS

ONESOURCE Determination has detailed requirements for the following:

- Computer hardware
- Operating system
- Database
- Application server/web container

To confirm you are using supported components, review platform support and product support lifecycle information listed in [Indirect Tax Help and Support](#).

JAVA

Determination requires an application server to host its various components, and the application server must use Oracle Java (1.8, 1.10 or 1.11) or Amazon Corretto (1.8.x or 11). Search [Indirect Tax Help and Support](#) to find the platform support information specific to your product version. If your application server does not provide its own version of Java or Amazon Corretto, you must install it separately.

GATHERING ADMINISTRATIVE INFORMATION

To install the Determination software, you need to gather certain administrative information. Before you begin the installation, add your values to the table below:

RESOURCES

Type	Where to Find	Your Values(s)
Customer Center credentials	Thomson Reuters Customer Support	
Oracle RDBMS server name and service name	Oracle DBA	
Administration credentials for Oracle database (sys account access)	Oracle DBA	
Name of server hosting JBoss and the port for the Determination software (used to build the URL for the Determination software)	Application Server Administrator	

DOWNLOAD THE SOFTWARE

To download and install the software, get the *ONESOURCEIDTDetermination_513xx.zip* file from the Indirect Tax Customer Center:

1. Open the Indirect Tax Customer Center at <https://customercenter.sabrix.com/>.
2. Log on using the username and password provided by Customer Support.
3. Find Determination in the **Available Products** list and verify that **Installed Version** is set to **None**.
4. Select **Download** for Determination.
5. Save the file.
6. Unzip the *ONESOURCEIDTDetermination_513xx.zip* file.

CONFIGURING YOUR DATABASE

This guide covers the installation of Determination in the Oracle RDBMS. Once you have confirmed that you are using the correct database version for this release of Determination, review the following:

DATABASE INITIALIZATION PARAMETERS

Set the appropriate database initialization parameters for Determination. Contact Oracle if you need assistance setting these in your environment.



Set the Oracle parameter `OPEN_CURSORS` to 3000 to ensure the Determination installation completes successfully.

DATABASE CHARACTER SET

Configure the database to use a UTF8-compatible database character set. If you use the AL16UTF16 character set (default), multi-byte character handling performance will be optimized. You need to either install or upgrade the database to meet this requirement.

ORACLE TABLESPACES AND USERS

Oracle tablespaces and users must be created before you install Determination. You can use the .sql scripts provided in the downloaded .zip file to perform this task.

For production environments, you should create separate tablespaces to contain tax and audit data (SBXTAX and SBXAUD). If you accept the setup script defaults, these tablespaces are created automatically. The setup script also creates the users SBXTAX and SBXAUD. These user names are referred to throughout this document.



The tablespace creation script also enables you to create a single tablespace to hold all data. While this configuration may be desirable for a test environment, we do not recommend this for a production environment.

To create the required tablespace(s) and users:

1. On the system hosting the Oracle database, open a command prompt or terminal window.
2. Go to the directory containing the downloaded .sql scripts.

3. Log into SQL*Plus as SYS or SYSDBA.

4. Execute the following setup script:

```
@OracleDBSetup.sql
```



This script executes both the tablespace and user creation scripts. You can also execute these scripts separately, if desired.

5. Enter the path to the Determination datafile directory (without a trailing separator). The default shown is the directory containing default Oracle tablespaces on your system. Press ENTER to accept the default or enter a new path name.
6. Enter the path separator for your platform (" / " for Unix and Linux or " \ " for Microsoft Windows). The default should already be selected.
7. Enter values for the Tax and, optionally, the Audit schemas.
 - To accept the defaults (SBXTAX and SBXAUD are shown in this guide), press ENTER at each prompt.
 - To create a new schema, enter its name at each prompt.
 - To skip the schema creation, enter the value of **none** at each prompt.
8. Messages appear as the tablespaces are created.
9. You are prompted to verify the locations of the tablespaces created earlier. If you accepted the defaults above, the prompts would appear as the following:

Tablespace for Sabrix tax data [SBXTAX]:

Tablespace for Sabrix audit data [SBXAUD]:

Temporary Tablespace for Sabrix users [TEMP]:
10. You are prompted to create the user for the Tax schema. Press ENTER to specify the default (SBXTAX is used in this guide) or enter another desired name.
11. If you chose to create a separate Audit schema, press ENTER to specify the default user name (SBXAUD is used in this guide) or enter another desired name.
12. Enter a profile name for each user when prompted. If you are unsure which profile to use, enter **default**.
13. Messages appear as the user(s) are created.

PREPARING ORACLE FOR XA TRANSACTIONS

To ensure that your Determination installation handles XA transactions, execute the following database grants for both the Tax (SBXTAX) and Audit (SBXAUD) users. Replace **SBXTAX** and **SBXAUD** with the Tax and Audit schemas from your environment:

```
1 GRANT SELECT ON sys.dba_pending_transactions TO SBXTAX;  
2 GRANT SELECT ON sys.pending_trans$ TO SBXTAX;  
3 GRANT SELECT ON sys.dba_2pc_pending TO SBXTAX;  
4 GRANT EXECUTE ON sys.dbms_xa TO SBXTAX;
```

```
1 GRANT SELECT ON sys.dba_pending_transactions TO SBXAUD;  
2 GRANT SELECT ON sys.pending_trans$ TO SBXAUD;  
3 GRANT SELECT ON sys.dba_2pc_pending TO SBXAUD;  
4 GRANT EXECUTE ON sys.dbms_xa TO SBXAUD;
```


CONFIGURING JBOSS ENTERPRISE EDITION

Before you proceed to the following tasks, ensure that you have a supported version of JBoss by reviewing platform support information listed in [Indirect Tax Help and Support](#).



Be sure you installed JBoss according to their instructions, and confirm that your JAVA_HOME operating system environment variable is pointing to the Java installation directory.

The following instructions are for a standalone installation of JBoss Enterprise. If you have a domain, please consult your JBoss documentation.

When JBoss is installed and ready for Determination configuration, complete the following:

[Modifying the Start-Up Parameters \(page 11\)](#)

[Unix Example \(page 12\)](#)

[Microsoft Windows Example \(page 13\)](#)

[Creating Data Sources \(page 13\)](#)


[Controlling HTTP Parameters \(page 17\)](#)



[JDBC Driver \(page 18\)](#)

[Deploying the Application \(page 18\)](#)

MODIFYING THE START-UP PARAMETERS

Locate *standalone.conf* (Unix) or *standalone.conf.bat* (Microsoft Windows) in the *bin* directory of your *<JBossHomeDirectory>*, and then open it in a text editor. The table below contains options and values in the file that you will change or add. See the examples for your operating system below.

JAVA OPTION	VALUE	DESCRIPTION
-Xms	2048m	<p>Increase this starting value to at least this amount.</p> <p> We recommend allocating at least 6144m.</p>

JAVA OPTION	VALUE	DESCRIPTION
-Xmx	2048m	<p>Increase this maximum value to at least this amount.</p> <p> We recommend allocating at least 6144m.</p>
-DBASE_SABRIX_DIRECTORY=	Directory path for logging	<p>If you plan to run Determination in several instances of the application server on the same host, add this parameter to ensure that each instance logs to its own directory. If you are only running one instance of the application server, you can skip this and set the parameter on the Configuration page of Determination (see the Help for further details).</p> <p>Insert this following the other options, and then replace <LoggingDirectory> with a directory path from your environment.</p> <p>UNIX:</p> <pre>JAVA_OPTS="\$JAVA_OPTS -DBASE_SABRIX_DIRECTORY=<LoggingDirectory>"</pre> <p>MICROSOFT WINDOWS:</p> <pre>set "JAVA_OPTS=%JAVA_OPTS% -DBASE_SABRIX_DIRECTORY=<LoggingDirectory>"</pre> <p> If you are using Microsoft Windows, use escape characters for the directory backslashes (for example, "c:\\temp\\").</p>

Unix Example

Locate the section in *standalone.conf* that begins with the following:

```
1 if [ "x$JAVA_OPTS" = "x" ]; then
```

Change or add the values in bold text below. This example is for the Java HotSpot VM.

```
1 if [ "x$JAVA_OPTS" = "x" ]; then
2     JAVA_OPTS="-Xms2048m -Xmx2048m -Djava.net
   .preferIPv4Stack=true"
3     JAVA_OPTS="$JAVA_OPTS -Djboss.modules.system.pkgs=$JBoss_MODULES_SYSTEM_PKGS -Djava.awt.headless=true"
4     JAVA_OPTS="$JAVA_OPTS -Djboss.modules.policy-permissions=true"
5 else
```

Microsoft Windows Example

Locate the section in *standalone.conf.bat* that begins with the following:

```
1 rem # JVM memory allocation pool parameters - modify as  
appropriate.
```

Using the table of Java options as a guide, insert your values into the section shown below. This example is for the Java HotSpot VM.

```
1 rem # JVM memory allocation pool parameters - modify as  
appropriate.  
2 set "JAVA_OPTS=-Xms2048m -Xmx2048m"
```

CREATING DATA SOURCES


Locate the file *standalone.xml* in the *configuration* directory under *standalone*, and then open it in a text editor.

You need to insert our data source snippet into *standalone.xml*. Use the snippet sections below to create your own text file:

1. Open a text editor, such as Windows Notepad.
2. Copy then paste into the text editor all lines of the tax data source and audit data source snippet sections, which are located below each table.
3. In the text editor, save the file with a file name of *jboss-oracle-xa-ds_example.txt*.


Insert the entire data source snippet between the `<datasources>` elements in *standalone.xml*. Follow the steps in the sections below for editing values in the snippet.

Tax Data Source: Change the values in the snippet that correspond to the elements in the table below. The sample snippet that follows the table has bold entries highlighting the values to change.

TAX DATA SOURCE (JDBC/TAXDATASOURCE)	
Element	Description
<pre><xa-datasource-property name="URL"> jdbc:oracle:thin:@host:port:service </xa-datasource-property></pre> <div>  <p>For Oracle Database 19c (19.6) Enterprise Edition platforms - support starting as of Determination 5.12.1.0 and above - the URL should be:</p> <p>jdbc:oracle:thin:@host:port/service</p> </div>	<p>Replace the following with values for your implementation:</p> <ul style="list-style-type: none"> • host: The name of the system hosting the database. • port: The database port; the default is 1521. • service: The name of your Oracle service.
<pre><driver>jdbc</driver></pre>	Replace jdbc with the name of the JDBC driver (for example, <i>ojdbc8.jar</i>).
<pre><user-name>user name</user-name></pre>	Replace user name with the Tax schema user name (for example, SBXTAX).
<pre><password>password</password></pre>	Replace password with the Tax schema password (for example, SBXTAX).

```
1 <xa-datasource jndi-name="java:/jdbc/TaxDataSource" pool-name="TaxDataSourceDS" enabled="true" use-java-context="true">
2   <xa-datasource-property name="URL">
3     jdbc:oracle:thin:@host:port:service
4   </xa-datasource-property>
5   <xa-datasource-class>
6     oracle.jdbc.xa.client.OracleXADataSource
7   </xa-datasource-class>
8   <driver>jdbc</driver>
9   <xa-pool>
10    <min-pool-size>16</min-pool-size>
11    <max-pool-size>64</max-pool-size>
12    <is-same-rm-override>false</is-same-rm-override>
13    <no-tx-separate-pools>true</no-tx-separate-pools>
14  </xa-pool>
15  <security>
16    <user-name>user name</user-name>
17    <password>password</password>
18  </security>
19  <validation>
20    <valid-connection-checker class-name="org.jboss.jca.adapters.jdbc.extensions.oracle.OracleValidConnectionChecker"/>
21    <stale-connection-checker class-name="org.jboss.jca.adapters.jdbc.extensions.oracle.OracleStaleConnectionChecker"/>
22    <exception-sorter class-name="org.jboss.jca.adapters.jdbc.extensions.oracle.OracleExceptionSorter"/>
23  </validation>
24  <statement>
25    <track-statements>true</track-statements>
26  </statement>
27 </xa-datasource>
```

Audit Data Source: Change the values in the snippet that correspond to the elements in the table below. The sample snippet that follows the table has bold entries highlighting the values to change.

AUDIT DATA SOURCE (JDBC/AUDITDATASOURCE)	
Element	Description
<pre><xa-datasource-property name="URL"> jdbc:oracle:thin:@host:port:service </xa-datasource-property></pre> <div>  <p>For Oracle Database 19c (19.6) Enterprise Edition platforms - support starting as of Determination 5.12.1.0 and above - the URL should be:</p> <p><code>jdbc:oracle:thin:@host:port/service</code></p> </div>	<p>Replace the following with values for your implementation:</p> <ul style="list-style-type: none"> • host: The name of the system hosting the database. • port: The database port; the default is 1521. • service: The name of your Oracle service.
<pre><driver>jdbc</driver></pre>	Replace jdbc with the name of the JDBC driver (for example, <i>ojdbc8.jar</i>).
<pre><user-name>user name</user-name></pre>	Replace user name with the Audit schema user name (for example, SBXAUD).
<pre><password>password</password></pre>	Replace password with the Audit schema password (for example, SBXAUD).

```
1 <xa-datasource jndi-name="java:/jdbc/AuditDataSource" pool-name="
  AuditSourceDS" enabled="true" use-java-context="true">
2   <xa-datasource-property name="URL">
3     jdbc:oracle:thin:@host:port:service
4   </xa-datasource-property>
5   <xa-datasource-class>
6     oracle.jdbc.xa.client.OracleXADataSource
7   </xa-datasource-class>
8   <driver>jdbc</driver>
9   <xa-pool>
10    <min-pool-size>16</min-pool-size>
11    <max-pool-size>64</max-pool-size>
12    <is-same-rm-override>false</is-same-rm-override>
13    <no-tx-separate-pools>true</no-tx-separate-pools>
14  </xa-pool>
15  <security>
16    <user-name>user name</user-name>
17    <password>password</password>
18  </security>
19  <validation>
20    <valid-connection-checker class-name="org.jboss.jca.adapte
      rs.jdbc.extensions.oracle.OracleValidConnectionChecker"/>
21    <stale-connection-checker class-name="org.jboss.jca.adapte
      rs.jdbc.extensions.oracle.OracleStaleConnectionChecker"/>
22    <exception-sorter class-name="org.jboss.jca.adapters.jdbc.
      extensions.oracle.OracleExceptionSorter"/>
23  </validation>
24  <statement>
25    <track-statements>true</track-statements>
26  </statement>
27 </xa-datasource>
```

When you finish creating the data sources, continue to the next section to make an additional change in *standalone.xml*.

CONTROLLING HTTP PARAMETERS

Continue editing *standalone.xml* by adding a configuration that controls the number of HTTP parameters:

1. Locate the `</extensions>` tag in *standalone.xml*.
2. Below the `</extensions>` tag, insert the following:

```
1 <system-properties>
2   <property name="org.apache.tomcat.util.http.Parameters.MAX_
   COUNT" v
   alue="10000"/>
3 </system-properties>
```

3. Save and close the file.

JDBC DRIVER

Determination requires the latest JDBC driver version for your database. Locate the Oracle JDBC driver *ojdbc8.jar*, and copy it into the JBoss *deployments* directory under *standalone*.



JDBC drivers are usually packaged with the database or database client software.

DEPLOYING THE APPLICATION

The Determination application is contained in the *sabrix.ear* file, which is in the root directory of the Determination software. Copy this file to the *deployments* directory under *standalone*.

Start JBoss to deploy the application.

DUPLICATE USERS

Determination does not support duplicate user name entries in the database. During the installation process, the installer checks for duplicate user names. When duplicate users are found, the installer appends "_DET513x_[Sequential Number]" to those entries. For example, two entries for SMITH become SMITH_DET513x_1 and SMITH_DET513x_2.

If found, the installer displays a list of duplicate user names and the new replacement names.

```
5 duplicate user names found. Renamed the inactive duplicate data. | User Name |
Renamed User Name | | BobSmith | BobSmith_DET513x_1 | | BobSmith | BobSmith_
DET513x_2 | | BobSmith | BobSmith_DET513x_3 | | MaryClark | MaryClark_DET513x_4 |
| MaryClark | MaryClark_DET513x_5|
```

If the installer cannot append a user name, the installation fails. Duplicate user names that cannot be resolved are left in the database and must be modified manually before completing the installation. A message similar to the following displays:

```
Aborting installation. 11 duplicate user names found with more than 60 characters
after appending DET513x and maximum duplicate user count. Please remove or rename
these inactive duplicate user manually. | User Name | | MarkHam | |MarkHam |
|MarkHam | |MarkHam | |MarkHam | |MaryHart | |MaryHart | |MaryHart |
|TomSmith123456 | |TomSmith123456 | |TomSmith123456 |
```


RUNNING THE IMPLEMENTER

The Implementer is the installation program for Determination and is the process you run after configuring your application server.



Set the Oracle parameter OPEN_CURSORS to 3000 to ensure the Determination installation completes successfully.

STARTING THE INSTALLATION

Open a browser and complete the following steps:

1. Go to the Determination installation URL (<http://<host>:<port>/sabrix/install>).
2. Enter the following user name and password: **dba/password**.
3. The Implementer page displays a summary of your environment.

Determination Implementer		
Database Vendor:	Tax Data Oracle - Oracle Database 12c Enterprise Edition Release 12...	Audit Data Oracle - Oracle Database 12c Enterprise Edition Release 12...
Driver Version:	12.1.0.1.0	12.1.0.1.0
Database Connection:	jdbc:oracle:thin:@pdxsasqa145.corp.ositax.com:152...	jdbc:oracle:thin:@pdxsasqa145.corp.ositax.com:152...
Database User:	TE9628	TE9628A
Sabrix Version Installed		
Sabrix Version To Be Installed		5.11.0.0.33.33
Click to start the installation:		<input type="button" value="Run"/>

4. Click **Run** to start the installation.

CHECKING THE INSTALLATION RESULTS

When the process runs, it records the results in your browser window and in a log file:

- **Browser Window:** You should see the following message at the end of the screen output: "Implementation completed successfully!" If you receive this message, you can continue with the remaining sections in this guide. However, if you see the following message, you should contact Customer Support : "Problem(s) encountered during implementation! Check the installation messages for more information."

- **Log File:** If you want more detailed information about installation messages, review the *sabrix.log* file. See "Log Files" in the *ONESOURCE Indirect Tax Determination User Guide* for instructions about finding the log.



If you review the log immediately after installing Determination, you can ignore any errors that appear from the beginning of the log until the entry that ends with "CleanUpRolesForCoreUsers." Any errors that appear after this log entry may be significant, and you should contact Customer Support.

INSTALLING TAX CONTENT

This is a two-step process that is composed of importing the content and associating that content with a Determination company.

IMPORTING CONTENT INTO DETERMINATION

You downloaded the Content file(s) at the beginning of this installation process. Now, you will import the files into Determination using the Import/Export feature.



Do not unzip your Content files. You will load these into Determination as zipped files.

1. Go to the Determination URL (<http://<host>:<port>/sabrix/>).
2. Enter the following user name and password: **dba/password**.



To protect your system, be sure to change the password for the dba user once you have completed the initial installation. See Help for details about how to change the password.

3. Go to **Menu > System > Import/Export**.
4. Click the **Import** tab.
5. Browse to the directory containing the first downloaded file.
6. Enter the path and file name, or browse to it, and then click OK.
7. Click **Import**.
8. The **Import/Export Wizard** displays information about the file to be imported. Click **Next**.
9. Click **Next** on each page until the import starts.
10. Once the import has started, close this status window - even though the import is not finished. The import will continue, and you can go to the **History** tab periodically to check the status. Click **Refresh** on the **History** tab to update the display.

11. Repeat steps 3 through 9 for the other Tax Data Provider(s), as appropriate.



Once you install master Content, you will need to perform monthly Content updates to keep your data current. You can automate all or part of the update process. For more information, see the "Import/Export" topic in Help.

CREATING AND CONFIGURING A COMPANY

To use the new Content, you need to associate it with a company in the Determination software.

1. Log on to Determination as the dba user.
2. Go to **Menu > System > Companies**.
3. Select **Add** from the **Actions** menu to create a company.
4. On the **Edit** tab, enter basic company information, and then click **Submit**.
5. Click the **Tax Preferences** tab.
6. In the **Data Providers** section, select values for your **Tax Data Provider**, and then click **Submit**.

You now have a basic Determination company to use when you test the installation in the following section. Once you successfully complete the testing, you can make additional company configurations (see the Help topic "Working with Companies").

TESTING YOUR INSTALLATION

After installing Determination and creating a basic company, test the installation by creating a test transaction.

1. Log on to Determination as the **dba** user.
2. Select the company you previously created from the **Company** selector in the upper right corner of the page.
3. Select **Menu > Workbench**.
4. Enter scenario information for a test transaction on the **Main** tab of the workbench. For example, enter the following:
 - **Scenario:** 1
 - **Invoice Number:** 1
 - **Company Role:** Seller
 - **Currency:** United States Dollar
 - **Quantity:** 1
 - **Gross Amt:** 1000
5. Click the **Locations** tab.
6. Click **Ship From**, and then enter the following:
 - **Ship From Country:** US
 - **Ship From State:** WA
 - **Ship From County:** KING
 - **Ship From City:** SEATTLE
 - **Ship From Zip:** 98101
7. Click **Ship To**, and then enter the following:
 - **Ship To Country:** US
 - **Ship To State:** CA

- **Ship To County:** ALAMEDA
 - **Ship To City:** OAKLAND
 - **Ship To Zip:** 94601
8. Click **Submit**. You should see an effective rate and tax amount for your transaction. Click **Results** to review the processing of the invoice including tax breakdowns per jurisdiction.
 9. Select **Input XML** or **Output XML** from the **Actions** menu to view the XML that was sent to and returned by the Determination software. These tools can be helpful if you need to debug the integration software that connects your financial system with Determination. See the *Programmer Guide* for more details.

CLUSTERING



Skip this section if you are not installing in a clustered environment.

Starting from Determination version 5.13.4.3, we recommend using Time Eviction Caching (Section below) instead of Clustering.

Due to upgrade of libraries in version 5.13.4.3, caching features are not supported.

- In the Running Implementer section above, when Run button is clicked, installer will not complete. As a work around, remove the node from cluster and then run the installer. After installer is complete, move node back to cluster.
- In System > Diagnostics > Cache View, caching entities are not displayed, and cache cannot be reset using the Reset Cache button. In case of any cache corruption please do the rolling restart of all nodes.

Determination supports TCP and UDP cluster communication to establish initial cluster membership, as well as to keep membership information current.

Review the following sections to set up clustering:

[Prerequisites \(page 27\)](#)

[Determination Parameters \(page 28\)](#)

[Module File \(page 29\)](#)

[Standalone File \(page 30\)](#)

[Properties File \(page 30\)](#)

[Cluster XML File \(page 34\)](#)

[Cluster Test \(page 35\)](#)

PREREQUISITES

Review the following before you begin configuring the cluster.

- **Tax Content:** Make sure your tax content is loaded into Determination before you set up the cluster.
- **JDBC URLs:** All cluster members must have identical JDBC URLs. For example, although the following two URLs point to the same host and database, clustering would not work because one JDBC URL uses the IP address and the other uses the fully qualified domain name for the host of the database:

```
jdbc:oracle:thin:@pdxsasdv062.corp.acme.com:1521/service
```

```
jdbc:oracle:thin:@10.198.221.48:1521/service
```

- **Internet Protocol Versions:** Some application servers default to the IPv6 stack while others use the IPv4 stack. When you enter IP addresses during the cluster configuration, be sure to adhere to the format appropriate for the internet protocol version. If your cluster involves communication between an IPv4 and an IPv6 node, set the following property in the start-up file of the application server:

```
1 -Djava.net.preferIPv4Stack=true
```

- **Firewalls:** Make sure firewalls are not blocking communications between Determination nodes.
- **Multicast:** If you are using multicast, confirm that the Determination nodes are on the same subnet, and that the network allows multicast packets to be transmitted.
- **Multihomed Host:** If there is a multihomed Ethernet configuration, force the use of a particular IP by setting the **jgroups.bind_address** system property to the appropriate NIC IP address. For example if the desired interface has an IP of 10.198.221.48, set the following Java system variable: `-Djgroups.bind_address=10.198.221.48`.












You can set **jgroups.bind_address** where the JVM parameters are set. Here is a configuration file example:

```
1 -Xms4096m -Xmx4096m -Djava.awt.headless=true -Djgroups.bind_
address=10.198.221.48
```

DETERMINATION PARAMETERS

Clustering requires certain parameters in Determination.

1. Log on to Determination.
2. Go to **Menu > System > Configuration**.
3. Click **Actions > Add**.
4. Enter the parameters and values according to the table below.

PARAMETER	VALUE	DESCRIPTION
ENABLE_SERVER_  COMMUNICATION	Y	This parameter is required to enable all types of clustering.
CLUSTER_ CHANNEL_  PROPERTIES_FILE	udp- cluster.xml or tcp-tcpping-  cluster.xml	<div> This parameter is not allowed if you are using UDP with default ports and IP addresses.</div> <div>If you are using UDP with non-default settings, insert the value udp-cluster.xml.</div> <div>If you are using TCP, insert the value tcp-tcpping-cluster.xml. This parameter must match the parameter <i>determination.infinispan.jgroups</i>. <i>configuration_file</i> in the <i>determination_application_</i> <i>overrides.properties</i> file. See Properties File (page 30).</div>
SABRIX_MASTER_ NODE		<div> If this parameter exists, remove it to set up clustering.</div>
MULTICAST_ ADDRESS		<div> If this parameter exists, remove it to set up clustering.</div>
MULTICAST_PORT		<div> If this parameter exists, remove it to set up clustering.</div>

5. Click **Submit**.

MODULE FILE

Complete the following:

1. Stop JBoss.
2. Create a new directory in JBoss:

```
<JBossHomeDirectory>/modules/com/thomsonreuters/config/main
```

3. In this new directory, create a file called *module.xml*, and insert the following lines:

```
1 <module xmlns="urn:jboss:module:1.1" name="com.thomsonreuters
  .config">
2   <resources>
3     <resource-root path="."/>
4   </resources>
5   <dependencies>
6     <module name="javaee.api" />
7   </dependencies>
8 </module>
```

4. Save and close *module.xml*.
5. Repeat these steps on each JBoss node.

STANDALONE FILE

Complete the following:

1. Go to the following directory:

<JBossHomeDirectory>/standalone/configuration

2. Open *standalone.xml* in a text editor.
3. Locate the following section:

<subsystem xmlns="urn:jboss:domain:ee:1.2">

4. Insert the following snippet as a child of the *subsystem* element above:

```
1 <global-modules>
2   <module name="com.thomsonreuters.config" slot="main" />
3 </global-modules>
```

5. Save and close *standalone.xml*.
6. Repeat these steps on each JBoss node.

PROPERTIES FILE

Determination requires a properties file for clustering, and the contents of the file depends on whether you are using UDP or TCP. Based on your network environment, follow the steps in one of the next three sections:

UDP Multicast with Default Settings

This section explains how to set up UDP multicast with the following defaults:

- Multicast Address = 224.0.0.1
- Multicast Port = 5665



If you have multiple clusters of Determination on the same subnet (for example, Production, Development, and QA), skip to the next section, [UDP Multicast with Non-Default IP and Port Number \(page 32\)](#). That approach prevents the clusters from interfering with each other.

Complete the following:

1. Go to the directory you created previously:

```
<JBossHomeDirectory>/modules/com/thomsonreuters/config/main
```

2. Create a new file called *determination_application_overrides.properties*, and then insert the following lines:

```
1 determination.infinispan.cache.configuration=infinispan.xml
2 determination.infinispan.jgroups.cluster_name=ClusterName
```

3. Replace **ClusterName** in the second line of the snippet with a unique name for your cache cluster.



Be sure to use the same cluster name in the *determination_application_overrides.properties* file on each node, and do not include any spaces in your cluster name.

4. Save and close the file *determination_application_overrides.properties*.
5. Restart JBoss.
6. Repeat these steps on each JBoss node.



To simplify the process, you can copy the file *determination_application_overrides.properties* to each node.

7. Skip to [Cluster Test \(page 35\)](#).

UDP Multicast with Non-Default IP and Port Number

This configuration changes the default UDP multicast address and port in cases when default values are not appropriate.



Ensure that you created the Determination parameter `CLUSTER_CHANNEL_PROPERTIES_FILE` before completing these steps. See [Determination Parameters \(page 28\)](#).

Complete the following:

1. Go to the directory you created previously:

```
<JBossHomeDirectory>/modules/com/thomsonreuters/config/main
```

2. Create a new file called *determination_application_overrides.properties*, and then insert the following lines:

```
1 determination.infinispan.cache.configuration=infinispan.xml
2 determination.infinispan.jgroups.cluster_name=ClusterName
3 determination.infinispan.jgroups.configuration_file= udp-clust
  er.xml
4 determination.infinispan.jgroups.udp.mcast_addr=224.1.2.3
5 determination.infinispan.jgroups.udp.mcast_port=16655
```

3. Replace **ClusterName** in the second line of the snippet with a unique name for your cache cluster.



Be sure to use the same cluster name in the *determination_application_overrides.properties* file on each node and do not include any spaces in your cluster name.

4. Change the numbers for **mcast_addr** and **mcast_port** to match your multicast address and port. Be sure to use valid ranges (Addr: 224.0.1.0 to 238.255.255.255).
5. Save and close the file *determination_application_overrides.properties*.
6. Repeat these steps on each JBoss node.



To simplify the process, you can copy the file *determination_application_overrides.properties* to each node.

7. Skip to [Cluster XML File \(page 34\)](#).

TCP Transport with Static List of Nodes (TCPPING)

In this configuration, a static list of cluster member addresses is set on each node so each member knows where the other cluster members are located.



Ensure that you created the Determination parameter `CLUSTER_CHANNEL_PROPERTIES_FILE` before completing these steps. See [Determination Parameters \(page 28\)](#).

Complete the following:

1. Go to the directory you created previously:

```
<JBossHomeDirectory>/modules/com/thomsonreuters/config/main
```

2. Create a new file called *determination_application_overrides.properties*, and then insert the following lines:

```
1 determination.infinispan.cache.configuration=infinispan.xml
2 determination.infinispan.jgroups.cluster_name=ClusterName
3 determination.infinispan.jgroups.configuration_file=tcp-tcpping-cluster.xml
4 determination.infinispan.jgroups.tcp.address=10.198.221.48
5 determination.infinispan.jgroups.tcpping.initial_hosts=10.198
  .221.50[7800],10.198.221.48[7800]
6 determination.infinispan.jgroups.tcp.port=7800
```

3. Replace **ClusterName** in the second line of the snippet with a unique name for your cache cluster.



Be sure to use the same cluster name in the *determination_application_overrides.properties* file on each node and do not include any spaces in your cluster name.

4. Set **tcp.address** to match the node's IP address.
5. Set **tcpping.initial_hosts** to list the addresses of all nodes in the cluster. The value of **tcpping.initial_hosts** is the same on each node, but **tcp.address** is unique for each node.



[7800] refers to the port on which each cluster instance will start the initial membership lookup. If necessary, you can change the port ranges by editing *tcp-tcpping-cluster.xml* (see [Cluster XML File \(page 34\)](#)). Change the two values of 7800 specified in the file to some other valid and available port to complete this change.

6. To change the default port from 7800, set **tcp.port** to the new port value.



If you use the default port of 7800, do not include this entry in the properties file.

If you specify the **tcp.port** property, the port number used for this property should match the port number used in the **tcpping.initial_hosts** property.

7. Save and close the file *determination_application_overrides.properties*.
8. Repeat the process for all nodes in the cluster, making all specified values identical except **tcp.address** which should be unique per node.



In this configuration, when a new cluster member is introduced or an existing one is removed, the list must be updated on each node. An update requires cluster nodes to be restarted so new changes are picked up. You add to the list or subtract from the list by adding or removing additional IP addresses in *determination_application_overrides.properties* at this line:

```
1 determination.infinispan.jgroups.tcpping.initial_hosts=
  10.198.221.50[7800],10.198.221.48[7800]
```


CLUSTER XML FILE



This step does not apply to UDP clusters that use default ports and IP addresses.

Complete the following to set up the cluster XML file:

1. Go to the *clustering* directory where you unzipped the *ONESOURCEIDTDetermination_513xx.zip* file (see [Download the Software \(page 6\)](#)).
2. Use the table below to determine which XML file from the *clustering* directory is appropriate for your environment.

FILE NAME	CLUSTER TYPE
udp-cluster.xml	UDP  This is only for UDP clusters that use custom ports and IP addresses.
tcp-tcpping-cluster.xml	TCP

3. Copy the appropriate XML file to the same directory as *determination_application_overrides.properties*:

```
<JBossHomeDirectory>/modules/com/thomsonreuters/config/main
```


4. Restart JBoss.
5. Repeat these steps on each node.

CLUSTER TEST

Complete the following tests to confirm that clustering is configured correctly.



If the tests fail, please double-check your settings before contacting Customer Support.

Verify that cluster members can send and receive messages:

1. After all cluster nodes are started, log on to Determination on one node and go to **Menu > System > Diagnostics > Cluster View**. The page should list all nodes in the cluster.
2. Click **Actions > Send Test Message**.
3. Log on to each of the other cluster members and go to **Menu > System > Diagnostics > Cluster View**. Confirm that each node received the message (you may need to click **Actions > Refresh**).
4. Repeat these steps from each node to ensure each node can send and receive messages.



Skip this below section for versions starting from 5.13.4.3.

Verify that resetting the cache on one node resets all caches in the cluster:

1. Populate the Determination cache by clicking **Menu > System > Companies** on each node.
2. On each of the cluster nodes, go to **Menu > System > Diagnostics > Cache View**.
3. Enter **ALL** in the **Table Name or 'ALL'** field then click **Search**. The cache content is displayed on each node.
4. On any cluster node, click **Actions > Reset Cache**, and then perform another search for **ALL** on the other nodes. If you have not accessed any other pages, the list should be empty (no entity has been cached).

TIME EVICTION CACHE

Complete the following:

1. Stop JBoss.
2. Go to the *clustering* directory where you unzipped 513xx (see [Download the Software \(page 6\)](#)).
3. Copy the *infinispan-timed-cache.xml* file to the directory -
<JBossHomeDirectory>/modules/com/thomsonreuters/config/main



The **expiration lifespan="600000"** value determines the cache retention time in *milliseconds*. Change this value as per appropriate time that caching needs to be retained.

4. Go to the directory you created previously:

<JBossHomeDirectory>/modules/com/thomsonreuters/config/main
5. Create a new file called *determination_application_overrides.properties*, and then insert the following lines:

`determination.infinispan.cache.configuration=infinispan-timed-cache.xml`
6. Save and close the file *determination_application_overrides.properties*.
7. Restart JBoss.
8. Repeat these steps on each JBoss node.

PERFORMING ADDITIONAL CONFIGURATIONS

Once you verify that ONESOURCE Indirect Tax Determination is running, you may need to complete some post-installation tasks:

- Connecting your Determination instance to your business source system using integration software. Contact your implementation partner for assistance.
- Securing your Determination installation. See the Determination Help topic "Security Measures."
- Modifying Configuration parameters to reflect your hardware, network, and security environment. You can also modify those parameters that affect auditing, tax calculations, and reporting. See the Help topic "Configuration."
- Setting up users to access Determination. This might include tax professionals, tax clerks, and Determination administrators. See the Help topic "Edit Users."
- Completing the Company configuration you began in the section "Creating and Configuring a Determination Company." See the Help topic "Working With Companies."
- Installing and configuring ONESOURCE Indirect Tax Reporting. See the Help topic "Running Reports."